

ROOF: VERANDAH: EXTERNAL CLADDING: WINDOWS: FLOORING: BEARERS/JOISTS: FRAME/TRUSS: SITE FALL/INSPECTIONS: ELECTRICAL:

DOWNPIPES/TANKS: INTERNAL FITTINGS:

- Rangehood
- Oven
- Cooktop
- Kitchen Sink
- Laundry Tub
- Toilet Suite
- Vanity Unit to Bathroom
- Bath
- Shower Base
- Shower Screen
- Mirror
- Taps
- Bathroom Accessories
- Hot Water System
- Built-In Robes
- Door Handles
- Paintwork

FLY SCREEN DOORS: KITCHEN:

INSULATION:

TILING:

CORNICE:

	bullnose roof and deck to front elevation with hip returns
Hardiplan	x Woodgrain (staggered ends)
	Sliding, including flyscreens and key locks (standard colours only)
Approved	water resistant and termite treated Aquabar sheeting
Cypress Pi	
Termite tre	ated timber
	subject to inspection)/First site inspection free
18 light po (2) downliç	ints, including round LED light to kitchen & Tastic 2 Heat to bathroom; and two yhts
14 double	power points with earth leakage
Two (2) TV	points
Two (2) sm	oke detectors
No allowa	nce, outlets only
600mm slid	de out (stainless steel)
Combinatio	on under bench (stainless steel)
Solid elect	ric plates or gas (stainless steel) – (Supply Only for Gas Cooktop)
Flushline 1	/2 bowl & drainer (stainless steel)
70 litre Tul	0
4 Star Prin	na Suite (white)
Tammarq 9	200mm
1500mm (v	white)
900mm x 9	200mm (white)
Pivot door;	clear glass; and semi frameless
900mm	
Flick Mixer	
Projix Rang	ge: Soap dish; double towel rail; and toilet roll holder
Rheem Inte	grity instantaneous gas – supply only, owner to install on site
2.400 l/m	to bedroom one (1); 2.100 l/m to bedroom two (2) with sliding doors
Lever (Sati	n Chrome)
Allowance internal wo	for five (5) white based colours: exterior; ceiling (white); trims; wet areas; and Ills
Security sc	reens to front and rear external doors
	of 600mm wide bench top, including breakfast bar; 2.560 I/m overhead , including rangehood cupboard with bulkhead to ceiling; and built-in corner
R4.0 to cei Foil to subf	ling; R2.5 & Breather Foil to external walls; Thermofoil to roof; and R2.0 & Silve loor
2.0m high	to shower and 1.2m to balance of bathroom (depending on tile size)
One (1) ro	w of skirting tile to WC and laundry
Splash-bad	k to laundry tub
Ceramic fle	por tiles throughout wet areas
	k to kitchen (approximately 600mm high)